Diamond Washed Hide Salt

with 1% Boric Acid and 1% Sodium Fluoride

Product Description

Diamond Washed Hide Salt with 1% Boric Acid and 1% Sodium Fluoride is a dried, refined salt (sodium chloride), crushed and sieved then mixed with chemicals for the use in the hide and skins industry only. It is produced in Australia by natural solar evaporation, harvested and refined in accordance with good manufacturing practice, under a quality system that complies with ISO 9001.

*Note: This product is intended purely for the treatment of hides and skins and does contain an additive that, by itself, is considered hazardous (i.e. sodium fluoride, a class 6.1 poison). This product is not classified as hazardous under the Worksafe Australia criteria. Although the level of additives is insufficient for the mixture to be classified as hazardous under the Worksafe Australia criteria, this product must not be used for any other purpose.

This product is not for human or animal consumption, it should be stored away from food products

Storage Conditions

Product is shelf life stable. Long-term storage does not adversely affect salt except for caking or lumping as salt absorbs/expels moisture from/to the atmosphere. Fine grain salts are particularly susceptible to caking. As a guide this product should be used within 12 - 24 months from manufacture date to avoid significant caking problems, however customers should assess their own individual needs for ordering frequency, stock rotation, stock levels



Issued: 28 September 2020

Chemical Analysis	
Purity (% NaCl min dry basis)	99.5
Moisture (% max)	3.0
Insolubles (% max)	0.10
Magnesium (mg/kg max)	500
Calcium (mg/kg max)	600
* Prior to the addition of additi	ves

Grainsize (Cummulative % Retained)

	Min.	Max.
11.2 mm	0 %	5 %
8.0 mm	0 %	10 %
0.85 mm	80 %	100 %
through 0.85 mm not greater than 20 %		

Additives		
Boric Acid	1.0 % minimum	
Sodium Fluoride	1.0 % minimum	

Country of Origin

Salt = Australia Boric Acid Sodium Fluoride

Palletising - Standard		
Bag Size	25kg net	25kg net
	weight	weight
Pallet type	Chep	Disposible
Bags per pallet	48 bags	48 bags
Pallet Weight	1.2 tonne	1.2 tonne
* Also available in other pack sizes by negotia	ition	

Protection and Labelling

Packed and sealed in woven polypropylene bags
Bonded internal laminate
Pallet slip sheet
Stretch wrapped

Traceability: date of manufacture as a minimum DD/MM/YY; or batch number which includes DOM in format YYMMDD,-BCH- then an automated sequential number i.e. YYMMDD-BCH-123456; printed on the side of individual bags as well as on pallet label

Method of Ar	alysis		
Purity	ASTM E 534 Standard Test Methods for Chemical Analysis		
	of Sodium Chloride "Reporting And Analysis".		
Moisture	AS 2093.1977 Appendix B		
Insolubles	ASTM E 534 "Water Insolubles" (100g used, results		
	reported to 0.001%)		
Calcium and	Reference: ASTM International Standard E 534 "Calcium		
Magnesium	Magnesium" Used" Japan Tobacco & Salt: Methods For		
	Salt Analysis Item 5.1 "Calcium & Magnesium" (atomic		
	absorption)		
Grainsize	AS 3638 Test Sieving Procedures		

